



Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Plate Caster, model _____. Resilient or polyurethane tread. Casters with zinc, stainless steel, and polymer boot available. 5" to 8" wheel diameter.

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Plate Casters

MODELS:

- CPS*-*
- CPB*-*
- CPR*-*
- CPS*P-*
- CPB*P-*
- CPR*P-*
- CPR*P-*
- CPL*Z-*
- CPS*Z-*
- CPR*Z-*
- CPB*Z-*
- PCPS5-250
- PCPL5-250
- CPS5S-300
- CPB5S-300


* See charts for complete model numbers.



resilient plate caster

Casters with Resilient Tread

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CPS5-200	200	90.7	5"	127	1 1/8"	29	2.8	1.3
brake	CPB5-200	200	90.7	5"	127	1 1/8"	29	2.8	1.3
rigid	CPR5-200	200	90.7	5"	127	1 1/8"	20	2.8	1.3
swivel	CPS5-250	250	113.4	5"	127	1 1/4"	32	3.0	1.4
brake	CPB5-250	250	113.4	5"	127	1 1/4"	32	3.0	1.4
rigid	CPR5-250	250	113.4	5"	127	1 1/4"	32	3.0	1.4
swivel	CPS6-500	500	226.8	6"	152	2"	51	9.0	4.1
brake	CPB6-500	500	226.8	6"	152	2"	51	9.0	4.1
rigid	CPR6-500	500	226.8	6"	152	2"	51	9.0	4.1



polyurethane plate
caster with brake

Casters with Polyurethane Tread

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CPS5P-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
brake	CPB5P-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
rigid	CPR5P-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
swivel	CPS5P-500	500	226.8	5"	127	2"	51	8.0	3.6
brake	CPB5P-500	500	226.8	5"	127	2"	51	8.0	3.6
rigid	CPR5P-500	500	226.8	5"	127	2"	51	8.0	3.6
swivel	CPS6P-600	600	272.1	6"	152	2"	51	9.0	4.1
brake	CPB6P-600	600	272.1	6"	152	2"	51	9.0	4.1
rigid	CPR6P-600	600	272.1	6"	152	2"	51	9.0	4.1
swivel	CPS8P-700	700	317.5	8"	203	2"	51	10.5	4.8
brake	CPB8P-700	700	317.5	8"	203	2"	51	10.5	4.8
rigid	CPR8P-700	700	317.5	8"	203	2"	51	10.5	4.8

EAGLE GROUP
 100 Industrial Boulevard, Clayton, DE 19938-8903 USA
 Phone: 302-653-3000 • Fax: 302-653-2065
 www.eaglegrp.com

Foodservice Division: Phone 800-441-8440
MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB®** Division.
 Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com



Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com



Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Plate Casters



swivel/lock plate caster

Swivel/Lock Casters

Polyurethane tread.

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel/lock	CPL6Z-800	800	362.9	6"	152	2"	51	9.0	4.1
swivel	CPS6Z-800	800	362.9	6"	152	2"	51	9.0	4.1
rigid	CPR6Z-800	800	362.9	6"	152	2"	51	9.0	4.1
brake	CPB6Z-800	800	362.9	6"	152	2"	51	9.0	4.1
swivel/lock	CPL8Z-900	900	408.2	8"	203	2"	51	10.0	4.8
swivel	CPS8Z-900	900	408.2	8"	203	2"	51	10.0	4.8
rigid	CPR8Z-900	900	408.2	8"	203	2"	51	10.0	4.8
brake	CPB8Z-900	900	408.2	8"	203	2"	51	10.0	4.8



polymer
plate caster

Polymer Casters

Polyurethane tread.

type	model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	PCPS5-250	250	90.7	5"	127	1 1/4"	32	2.8	1.3
lock	PCPL5-250	250	90.7	5"	127	1 1/4"	32	2.8	1.3



stainless steel
pressure-washable
caster (with brake)

Stainless Steel Pressure-Washable Casters

Polyurethane tread.

type	model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CPS5S-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
brake	CPB5S-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A.
 ©2017 by Eagle Group

Rev. 03/17

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.