




Profit from the Eagle Advantage®


# Specification Sheet

## Short Form Specifications

Eagle Cantilever Shelving System to consist of 14 gauge regular or NSF continuously seam-welded uprights, ceiling brackets, and single- or double-knob brackets. For use with either wire or solid shelving (sold separately). Heavy duty "C" brackets available in grey epoxy, stainless steel, or aluminum finish. Heavy duty crossbraces available in grey epoxy or nickel finish.



single knob heavy duty "C" bracket—shown with wire shelf mounted



heavy-duty back-to-back upright



wall-mounted cantilevered shelving shown with wire shelving

Item No.:	_____
Project No.:	_____
S.I.S. No.:	_____

## Cantilevered Shelving System —Heavy Duty Components

### MODELS:

- |                                       |  |                                    |
|---------------------------------------|--|------------------------------------|
| <input type="checkbox"/> MMBC-K-*     | <input type="checkbox"/> MMDBC-K-*     | <input type="checkbox"/> MMBB-*    |
| <input type="checkbox"/> MMNSBC-K-*   | <input type="checkbox"/> MMNSDBC-K-*   | <input type="checkbox"/> MMNSBB-*  |
| <input type="checkbox"/> MMBCSS-K-*   | <input type="checkbox"/> MMDBCSS-K-*   | <input type="checkbox"/> MMBBSS*   |
| <input type="checkbox"/> MMNSBCSS-K-* | <input type="checkbox"/> MMNSDBCSS-K-* | <input type="checkbox"/> MMNSBBSS* |
| <input type="checkbox"/> MMBC-K/A-*   | <input type="checkbox"/> MMDBC-K/A-*   | <input type="checkbox"/> MMBB/A-*  |
| <input type="checkbox"/> MMNSBC-K/A-* | <input type="checkbox"/> MMNSDBC-K/A-* | <input type="checkbox"/> MMXB-*    |
|                                       |  | <input type="checkbox"/> MMXB-N-*  |

\* See charts on back page for complete model numbers.

- Designed with convenience in mind.
- Requires no post supports to get in the way, making shelf loading and unloading easier.
- For use with both wire and solid shelving.
- 100% usable shelving surface, from section to section, wall to wall, and front to back — no posts to restrict stock placement.
- Infinite height adjustability — no slots or keyholes to line up for leveling, and shimming is eliminated.
- Wall-mounted shelving requires no support from the floor — floor area is therefore open and easily maintained.
- Finishes available include grey epoxy, stainless steel, and aluminum.
- Regular and NSF-approved components available.
- All components are made of heavy gauge material.
- Heavy-duty, rugged construction.

See Spec Sheet #EG01.45A for Uprights.  
See Spec Sheet #EG01.45B for Brackets.

**EAGLE GROUP**  
100 Industrial Boulevard, Clayton, DE 19938-8903 USA  
Phone: 302-653-3000 • Fax: 302-653-2065  
www.eaglegrp.com

**Foodservice Division: Phone 800-441-8440**  
**MHC/Retail Display Divisions: Phone 800-637-5100**

For custom configuration or fabrication needs, contact our **SpecFAB® Division**.  
Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

## AUTOQUOTES



EG01.45C Rev. 02/16

**Spec sheets available for viewing, printing or downloading from our online literature library at [www.eaglegrp.com](http://www.eaglegrp.com)**

Eagle Foodservice Equipment, Eagle MHC, SpecFAB®, and Retail Display are divisions of Eagle Group. ©2016 by the Eagle Group



Item No.: \_\_\_\_\_  
 Project No.: \_\_\_\_\_  
 S.I.S. No.: \_\_\_\_\_

# Cantilevered Shelving System—Heavy Duty Components

## HEAVY DUTY “C” BRACKETS

For Weight Capacities, see chart at bottom of page.

### Heavy Duty Single Knob “C” Brackets

For dynamic loads. For use with wire or solid shelving. Available with flanges at top left or right. To order, add suffix “-L” (left bracket) or “-R” (right bracket) to model number. Example: MMBC-K-18-L

length in. mm	GREY EPOXY			STAINLESS STEEL			ALUMINUM		
	REGULAR model #	NSF model #	weight lb. kg	REGULAR model #	NSF model #	weight lb. kg	REGULAR model #	NSF model #	weight lb. kg
18" 457	MMBC-K-18	MMNSBC-K-18	3 1.4	MMBCSS-K-18	MMNSBCSS-K-18	2 0.9	MMBC-K/A-18	MMNSBC-K/A-18	1 0.5
21" 533	MMBC-K-21	MMNSBC-K-21	3 1.4	MMBCSS-K-21	MMNSBCSS-K-21	3 1.4	MMBC-K/A-21	MMNSBC-K/A-21	1 0.5
24" 610	MMBC-K-24	MMNSBC-K-24	3 1.4	MMBCSS-K-24	MMNSBCSS-K-24	3 1.4	MMBC-K/A-24	MMNSBC-K/A-24	2 0.9

### Heavy Duty Double Knob “C” Brackets

For dynamic loads. For use with wire or solid shelving. With flanges on top left and right, these brackets support two adjoining shelves on a common upright.

length in. mm	GREY EPOXY			STAINLESS STEEL			ALUMINUM		
	REGULAR model #	NSF model #	weight lb. kg	REGULAR model #	NSF model #	weight lb. kg	REGULAR model #	NSF model #	weight lb. kg
18" 457	MMDBC-K-18	MMNSDBC-K-18	4 1.8	MMDBCSS-K-18	MMNSDBCSS-K-18	3 1.4	MMDBC-K/A-18	MMNSDBC-K/A-18	2 0.9
21" 533	MMDBC-K-21	MMNSDBC-K-21	4 1.8	MMDBCSS-K-21	MMNSDBCSS-K-21	4 1.8	MMDBC-K/A-21	MMNSDBC-K/A-21	2 0.9
24" 610	MMDBC-K-24	MMNSDBC-K-24	5 2.3	MMDBCSS-K-24	MMNSDBCSS-K-24	4 1.8	MMDBC-K/A-24	MMNSDBC-K/A-24	2 0.9

## HEAVY DUTY UPRIGHTS

Back-to-back, floor-to-ceiling, double-faced unitized uprights. Available in grey epoxy, stainless steel, or aluminum finish. Regular or NSF-approved.

height in. mm	GREY EPOXY			STAINLESS STEEL			ALUMINUM		
	REGULAR model #	NSF model #	weight lb. kg	REGULAR model #	NSF model #	weight lb. kg	REGULAR model #	weight lb. kg	
48" 1219	MMBB-4	MMNSBB-4	20 9.0	MMBBSS-4	MMNSBBSS-4	11 5.0	MMBB/A-4	14 6.4	
60" 1524	MMBB-5	MMNSBB-5	25 11.3	MMBBSS-5	MMNSBBSS-5	24 10.9	MMBB/A-5	17 7.7	
72" 1829	MMBB-6	MMNSBB-6	30 13.6	MMBBSS-6	MMNSBBSS-6	28 12.7	MMBB/A-6	21 9.5	
84" 2134	MMBB-7	MMNSBB-7	35 15.9	MMBBSS-7	MMNSBBSS-7	33 15.0	MMBB/A-7	24 10.9	
96" 2438	MMBB-8	MMNSBB-8	40 18.1	MMBBSS-8	MMNSBBSS-8	38 17.2	MMBB/A-8	28 12.7	
108" 2743	MMBB-9	MMNSBB-9	45 20.4	MMBBSS-9	MMNSBBSS-9	42 19.1	MMBB/A-9	31 14.1	
120" 3048	MMBB-10	MMNSBB-10	50 22.7	MMBBSS-10	MMNSBBSS-10	47 21.3	MMBB/A-10	34 15.4	
144" 3658	MMBB-12	MMNSBB-12	60 27.2	MMBBSS-12	MMNSBBSS-12	57 25.9	MMBB/A-12	41 18.6	

## HEAVY DUTY CROSSBRACES

Adds to stability of unit. 1" (25mm)-wide 7-gauge steel.

fits shelf length in. mm	crossbrace length in. mm	GREY EPOXY		NICKEL	
		model #	weight lb. kg	model #	weight lb. kg
36" 914	48" 1219	MMXB-48	2 0.9	MMXB-N-48	2 0.9
48" 1219	60" 1524	MMXB-60	3 1.4	MMXB-N-60	3 1.4
60" 1524	72" 1829	MMXB-72	4 1.8	MMXB-N-72	4 1.8
72" 1829	84" 2134	MMXB-84	5 2.3	MMXB-N-84	5 2.3

## WEIGHT CAPACITY PER BRACKET

Pertains to all brackets listed on this page.

bracket length in. mm	maximum load recommended lb. kg
18" 457	530 240.1
21" 533	450 204.1
24" 610	420 190.5

**EAGLE GROUP**  
 100 Industrial Boulevard, Clayton, DE 19938-8903 USA  
 Phone: 302-653-3000 • Fax: 302-653-2065  
 www.eaglegrp.com

Foodservice Division: Phone 800-441-8440  
 MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A.  
 ©2016 by Eagle Group  
 Rev. 02/16

Spec sheets available for viewing, printing or downloading from our online literature library at [www.eaglegrp.com](http://www.eaglegrp.com)

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.