



Profit from the Eagle Advantage®

# Specification Sheet

## Short Form Specifications

Eagle Director's Choice® Dish/Cup Dispenser Unit, model \_\_\_\_\_. Top to be 16/304 stainless steel turned down on all sides. 1½" square type 304 stainless steel all-welded tubular base. Quick release spring loaded docking device keeps adjoining units together. Heated unit to come with 5'-long cord(s) and plug(s). Fully mobile with 5" poly casters, two with brake. Standard laminate panel is holly berry red (Wilsonart® #D307-60).



model #DCS-PUD-4T  
(shown with optional tray slide)

## Options / Accessories

- Stainless steel end panels
- Stainless steel front panel
- Stainless steel tray slide\*
- Work shelf\*\*
- Specify laminate \_\_\_\_\_
- Dome covers (for heated units)

\* Available in solid ribbed, square tubular or round tubular. For front, rear, or ends.  
\*\* Available in maple, stainless steel, poly, or Richlite®. For front, rear, or ends.

**EAGLE GROUP**  
100 Industrial Boulevard, Clayton, DE 19938-8903 USA  
Phone: 302-653-3000 • Fax: 302-653-2065  
www.eaglegrp.com

**Foodservice Division: Phone 800-441-8440**  
**MHC/Retail Display Divisions: Phone 800-637-5100**

For custom configuration or fabrication needs, contact our **SpecFAB® Division**.  
Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Item No.: \_\_\_\_\_  
 Project No.: \_\_\_\_\_  
 S.I.S. No.: \_\_\_\_\_


## Director's Choice® Dish/Cup Dispensers

### MODELS:

- DCS-PUD-2TH
- DCS-PUD-3TH
- DCS-PUD-4TH
- DCS-PUD-5TH
- DCS-PUDT-CSH
- DCS-PUD-2T
- DCS-PUD-3T
- DCS-PUD-4T
- DCS-PUD-5T
- DCS-PUDT-CS
- 381250
- 381251
- 381252
- 381253

### Design and Construction Features

- 30" (762mm)-wide top is constructed of 16 gauge type 304 stainless steel, with required holes to accommodate dish/cup dispensers.
- Welded 1½" (38mm) type 304 stainless steel square tubular base construction.
- On heated units, temperature range is 80°–100°F minimum, 110°–160°F maximum.
- Dispensers included.
- Heated units include shielded dispensers, with 5' (1524mm)-long cord(s) and plug(s).
- Optional dome covers available for heated units.
- Fully mobile - standard 5" (127mm) poly tread casters, two with brake (brake casters on server side).
- Quick-release spring-loaded docking device keeps adjoining units together without the use of tools.
- Standard holly berry red (Wilsonart® D307-60) laminate mounted on 18 gauge galvanized subpanel on all four sides.
- End panels available in laminate or stainless steel.
- All units accommodate optional accessories, including tray slides, work shelves, and removable undershelves. See Catalog Sheet EG33.07.




**Spec sheets available for viewing, printing or downloading from our online literature library at [www.eaglegrp.com](http://www.eaglegrp.com)**




Profit from the Eagle Advantage®

Item No.: \_\_\_\_\_  
 Project No.: \_\_\_\_\_  
 S.I.S. No.: \_\_\_\_\_


## Director's Choice® Dish/Cup Dispensers




#DCS-PUD-2T and  
#DCS-PUD-2TH




#DCS-PUD-3T and  
#DCS-PUD-3TH



#DCS-PUD-4T and  
#DCS-PUD-4TH



#DCS-PUD-5T and  
#DCS-PUD-5TH



#DCS-PUDT-CS and  
#DCS-PUDT-CSH

### Heated Units

Includes shielded dispensers.

model #	description	heater— electrical data	dish/cup MAXIMUM diameter	weight		Applicable * Drop-In Dispenser
				lbs.	kg	model #
DCS-PUD-2TH	two-tube dispenser	760W, 120V or 208V	9 1/8" (232mm) plates	220	99.8	359129
DCS-PUD-3TH	three-tube dispenser	900W, 120V or 208V	7 1/4" (184mm) plates	270	122.5	359127
DCS-PUD-4TH	four-tube dispenser	1200W, 120V or 208V	7 1/4" (184mm) plates	320	145.2	359127
DCS-PUD-5TH	four-tube dispenser	1520W, 120V or 208V	9 1/8" (232mm) plates	350	158.8	359129
DCS-PUDT-CSH	cup/saucer dispenser, tubular type	800W, 120V or 208V	11 1/8" (302mm) plates	240	108.9	359131



### Optional Dome Covers for Heated Units

model #	for plate diameter of...		weight	
	in.	mm	lbs.	kg
381250	2 1/4"–6"	70–152	1	0.5
381251	4 1/4"–7 1/2"	108–191	1	0.5
381252	6 1/2"–9 3/4"	165–248	1	0.5
381253	8 3/4"–12"	222–305	1	0.5

### Non-Heated Units

Includes unshielded dispensers.

model #	description	dish/cup MAXIMUM diameter	weight		Applicable * Drop-In Dispenser
			lbs.	kg	model #
DCS-PUD-2T	two-tube dispenser	9 1/8" (232mm) plates	150	68.0	359111
DCS-PUD-3T	three-tube dispenser	7 1/4" (184mm) plates	165	74.8	359109
DCS-PUD-4T	four-tube dispenser	7 1/4" (184mm) plates	180	81.6	359109
DCS-PUD-5T	four-tube dispenser	9 1/8" (232mm) plates	210	95.3	359111
DCS-PUDT-CS	cup/saucer dispenser, tubular type	11 1/8" (302mm) plates	160	72.6	359113

\* See Specification Sheet #EG33.18 for more information on Drop-In Dispensers.

Optional stainless steel front panel in lieu of laminate front panel available. To order, add suffix "-S" to model number. Example: DSC3030-CO-S

Optional stainless steel end panels available. To order, add suffix "-SEP" to model number. Example: DSC3030-CO-S-SEP

### EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A.

©2019 by Eagle Group

Rev. 03/19

Spec sheets available for viewing, printing or downloading from our online literature library at [www.eaglegrp.com](http://www.eaglegrp.com)

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.